

Designed especially for the durability demands of high-touch environments, the lightly textured finish of Duets® Textures is engineered to resist the appearance of fingerprints, offer detailed engraving and extreme durability. Ideal for public spaces, high-traffic retail and industrial environments, Duets Textures is the perfect material for rugged outdoor or indoor signage and tagging applications.



Only the highest quality product leaves our plant. We manufacture Duets in our state-of-the-art cleanroom facility located in Cannon Falls, Minnesota allowing us to offer you a better product:

- Dust-free materials
- Tightly-controlled color and finish uniformity
- Consistently the flattest material

We stand behind everything that leaves our plant. And while it's our name on the materials, we know it's your name on the final product. That's a responsibility we don't take lightly.







APPLICATIONS

- Architectural Signage
- Egress / Exit Signage
- **■** Exterior Signage
- Interior Signage
- Industrial Signage
- Personal Identification
- Safety Signage
- Trophies, Awards & Plaques
- Wayfinding

CHARACTERISTICS

- Front Engravable
- Outdoor/Indoor
- UV Stable
- **■** UV Printable

SPECIFICATIONS Material Impact Modified Acrylic Finish Textured (non-glare) Thicknesses 2-ply: 1/16" (1.6mm) 2-ply: 1/8" (3.2mm) Engraving Methods Laser (may require two passes) or Rotary Engraving Depths .012" (.3mm) Sheet Sizes Sizes are approximate. Standard: 24" x 49" (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24" (305mm x 610mm)		
Finish Textured (non-glare) Thicknesses 2-ply: 1/16" (1.6mm) 2-ply: 1/8" (3.2mm) Engraving Methods Laser (may require two passes) or Rotary Engraving Depths .012" (.3mm) Sheet Sizes Sizes are approximate. Standard: 24" x 49" (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24"	SPECIFICATIONS	
Thicknesses 2-ply: 1/16" (1.6mm) 2-ply: 1/8" (3.2mm) Engraving Methods Laser (may require two passes) or Rotary Engraving Depths .012" (.3mm) Sheet Sizes Sizes are approximate. Standard: 24" x 49" (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24"	Material	Impact Modified Acrylic
2-ply: 1/8" (3.2mm) Engraving Methods Laser (may require two passes) or Rotary Engraving Depths .012" (.3mm) Sheet Sizes Sizes are approximate. Standard: 24" x 49" (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24"	Finish	Textured (non-glare)
passes) or Rotary Engraving Depths .012" (.3mm) Sheet Sizes Sizes are approximate. Standard: 24" x 49" (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24"	Thicknesses	
Sheet Sizes Sizes are approximate. Standard: 24" x 49" (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24"	Engraving Methods	
Sizes are approximate. (610mm x 1244mm) Half: 24" x 24" (610mm x 610mm) Quarter: 12" x 24"	Engraving Depths	.012" (.3mm)
Quarter: 12" x 24"		(610mm x 1244mm) Half: 24" x 24"
		Quarter: 12" x 24"

COLORS



